

Trade name: FotoTec Repair opaque

Substance number: 71028 Version: 1/GB Date revised: 14.03.2023

> Replaces Version: -/GB Print date: 14.03.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

FotoTec Repair opaque

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/preparation

Light-curing material for the production of earmolds

1.3. Details of the supplier of the safety data sheet

Address/Manufacturer

Dreve Otoplastik GmbH Max-Planck-Straße 31

59423 Unna

Telephone no. +49 2303 8807-0 Fax no. +49 2303 8807-29

Information provided Department Research & Development: Fax: +49 2303 8807-562

by / telephone

E-mail address of person responsible sicherheitsdatenblatt@dreve.de

for this SDS

1.4. Emergency telephone number

Henkel Fire Department / 24h-Emergency-Contact-No.: +49 211 797-3350

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (Regulation (EC) No. 1272/2008)

Classification (Regulation (EC) No. 1272/2008)

Skin Irrit. 2 H315 Eve Irrit. 2 H319 Skin Sens. 1 H317

The product is classified and labelled in accordance with Regulation (EC) No 1272/2008 For explanation of abbreviations see section 16.

2.2. Label elements

Labelling according to regulation (EC) No 1272/2008

Hazard pictograms



Signal word

Warning

Hazard statements

H315 Causes skin irritation.



Trade name: FotoTec Repair opaque

Substance number: 71028 Version: 1 / GB Date revised: 14.03.2023

Replaces Version: -/GB Print date: 14.03.2023

H319 Causes serious eye irritation. H317 May cause an allergic skin reaction.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264.1 Wash hands thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P501.1 Dispose of contents/container to industrial incineration plant.

Hazardous component(s) to be indicated on label (Regulation (EC) No. 1272/2008)

contains 2-hydroxyethyl methacrylate; 4,4'-lsopropylidenediphenol, oligomeric reaction

products with 1-chloro-2,3-epoxypropane, esters with acrylic acid; Hydroxylpropyl methacrylate; Propylidynetrimethanol, ethoxylated, esters with acrylic acid

2.3. Other hazards

No special hazards have to be mentioned.

The product contains no PBT substances. The product contains no vPvB substances. This product does not contain a substance that has endocrine disrupting properties with respect to human. The product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients

Aliphatic urethane methacrylate

Concentration >= 25 < 50 %

Classification (Regulation (EC) No. 1272/2008)

Eye Irrit. 2 H319

Hydroxylpropyl methacrylate

CAS No. 27813-02-1 EINECS no. 248-666-3

Registration no. 01-2119490226-37

Concentration >= 25 < 50 %

Classification (Regulation (EC) No. 1272/2008)

Eye Irrit. 2 H319 Skin Sens. 1 H317

ATE oral 2.000 mg/kg

2-hydroxyethyl methacrylate

CAS No. 868-77-9 EINECS no. 212-782-2

Registration no. 01-2119490169-29

Concentration >= 10 < 25 %

Classification (Regulation (EC) No. 1272/2008)

Skin Irrit. 2 H315 Eye Irrit. 2 H319 Skin Sens. 1 H317

Additional remarks:



Trade name: FotoTec Repair opaque

Substance number: 71028 Version: 1/GB Date revised: 14.03.2023

> Replaces Version: -/GB Print date: 14.03.2023

CLP Regulation (EC) No 1272/2008, Annex VI, Note D

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters

with acrylic acid

CAS No. 55818-57-0 EINECS no. 500-130-2

Registration no. 01-2119490020-53

Concentration 2.5 % >= 1 <

Classification (Regulation (EC) No. 1272/2008)

Skin Sens. 1 H317 Aquatic Chronic 2 H411

Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide

CAS No. 75980-60-8 EINECS no. 278-355-8

Registration no. 01-2119972295-29

Concentration % >= 0,1 1

Classification (Regulation (EC) No. 1272/2008)

Repr. 2 H361f

Propylidynetrimethanol, ethoxylated, esters with acrylic acid

CAS No. 28961-43-5 EINECS no. 500-066-5

Registration no. 01-2119489900-30

Concentration 0,1 % >=

Classification (Regulation (EC) No. 1272/2008)

Eye Irrit. 2 H319 Skin Sens. 1B H317 Aquatic Chronic 3 H412

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated clothing immediately and dispose of safely. Adhere to personal protective measures when giving first aid

After inhalation

Ensure supply of fresh air. Remove affected person from danger area. Seek medical advice immediately.

After skin contact

Wash off immediately with soap and water. Seek medical advice immediately.

After eye contact

Separate eyelids, wash the eyes thoroughly with water (15 min.). Take medical treatment.

After indestion

Call in a physician immediately and show him the Safety Data Sheet. Rinse mouth thoroughly with water. Let plenty of water be drunk in small gulps. Do not induce vomiting.

Adhere to personal protective measures when giving first aid

First aider: Pay attention to self-protection!

4.2. Most important symptoms and effects, both acute and delayed

Until now no symptoms known so far.



Trade name: FotoTec Repair opaque

Substance number: 71028 Version: 1 / GB Date revised: 14.03.2023

Replaces Version: -/GB Print date: 14.03.2023

4.3. Indication of any immediate medical attention and special treatment needed Hints for the physician / hazards

In the case of swallowing with subsequent vomiting, aspiration of the lungs can occur which can lead to chemical pneumonia or asphyxiation.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Recommended: alcohol resistant foam, CO2, powders, water spray/mist, Extinguishing measures to suit surroundings

Non suitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

In case of combustion evolution of dangerous gases possible.

5.3. Advice for firefighters

Special protective equipment for fire-fighting

Do not inhale explosion and/or combustion gases. In case of combustion use a suitable breathing apparatus. Wear full protective suit.

Other information

Collect contaminated fire-fighting water separately, must not be discharged into the drains. Fire residues and contaminated fire-fighting water must be disposed of in accordance with the local regulations. Observe manufacturer's / distributor`s instructions.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away sources of ignition. Ensure adequate ventilation. Use breathing apparatus if exposed to vapours/dust/aerosol. Avoid contact with skin, eyes and clothing. Use personal protective clothing. Refer to protective measures listed in Sections 7 and 8.

6.2. Environmental precautions

Prevent spread over a wide area (e.g. by containment or oil barriers). Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil. Retain and dispose of contaminated wash water. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Pick up rest with suitable absorbent materials. Do not pick up with the help of saw-dust or other combustible substances. Clean contaminated floors and objects thoroughly, observing environmental regulations. Containers in which spilt substance has been collected must be adequately labelled. Dispose of as prescribed.

6.4. Reference to other sections

Refer to protective measures listed in Sections 7 and 8.



Trade name: FotoTec Repair opaque

Substance number: 71028 Version: 1 / GB Date revised: 14.03.2023

Replaces Version: -/GB Print date: 14.03.2023

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Provide good ventilation of working area (local exhaust ventilation if necessary). Avoid formation of aerosols. Avoid impact, friction and electro-static loading; risk of ignition!. Keep container tightly closed.

Advice on protection against fire and explosion

Keep away from sources of heat and ignition. No smoking. Take action to prevent static discharges. Avoid impact and friction. Use only explosion-proof equipment. Keep away from combustible material. Wear shoes with conductive soles.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep in original packaging, tightly closed. Storage rooms must be properly ventilated. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Hints on storage assembly

Do not store together with foodstuffs. Do not store with strong oxidizing agents.

Further information on storage conditions

Keep under lock and key or accessible only to specialists or people who are authorized. Keep container tightly closed and in a well-ventilated place. Keep in a cool place

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Other information

Contains no substances with occupational exposure limit values.

Derived No/Minimal Effect Levels (DNEL/DMEL)

Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide

Type of value Derived No Effect Level (DNEL)

Reference group Worker
Duration of exposure Long term
Route of exposure dermal

Mode of action Systemic effects Concentration 0,233

Concentration 0,233 mg/kg/d

Type of value Derived No Effect Level (DNEL)

Reference group

Duration of exposure

Route of exposure

Mode of action

Consentration

Concentration 0,145 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group Consumer
Duration of exposure Long term
Route of exposure dermal

Mode of action Systemic effects

Concentration 0,0833 mg/kg/d



Trade name: FotoTec Repair opaque

Substance number: 71028 Version: 1/GB Date revised: 14.03.2023

> Replaces Version: -/GB Print date: 14.03.2023

Type of value Derived No Effect Level (DNEL)

Reference group Consumer Duration of exposure Long term Route of exposure oral

Mode of action Systemic effects Concentration 0.0833

mg/kg/d

2-hydroxyethyl methacrylate

Type of value Derived No Effect Level (DNEL)

Reference group Worker Duration of exposure Long term Route of exposure inhalative Mode of action Systemic effects

mg/m³ Concentration 4.9

Type of value Derived No Effect Level (DNEL)

Reference group Worker Duration of exposure Long term Route of exposure dermal

Mode of action Systemic effects

Concentration mg/kg/d 1,3

Derived No Effect Level (DNEL) Type of value

Consumer Reference group Duration of exposure Long term Route of exposure inhalative Mode of action

Systemic effects

Concentration 2,9 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group Consumer Long term Duration of exposure Route of exposure dermal

Mode of action Systemic effects

0.83 mg/kg/d Concentration

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid

Type of value Derived No Effect Level (DNEL)

Reference group Worker Duration of exposure Long term Route of exposure dermal

Mode of action Systemic effects

Concentration 17,5 mg/kg

Type of value Derived No Effect Level (DNEL)

Worker Reference group Duration of exposure Long term Route of exposure inhalative Mode of action

Systemic effects

Concentration 122,5 mg/m³

Hydroxylpropyl methacrylate

Reference substance Hydroxylpropyl methacrylate Type of value Derived No Effect Level (DNEL)

Reference group Worker



Print date: 14.03.2023

Trade name: FotoTec Repair opaque

Substance number: 71028 Version: 1/GB Date revised: 14.03.2023

Replaces Version: -/GB

Route of exposure inhalative

Concentration 14.7 mg/m³

Hydroxylpropyl methacrylate

Type of value Derived No Effect Level (DNEL)

Reference group Worker Route of exposure dermal

Concentration 4,2 mg/kg/d

Type of value Derived No Effect Level (DNEL)

Reference group Consumer Route of exposure dermal

Concentration 2,5 mg/kg

Type of value Derived No Effect Level (DNEL)

Reference group Consumer Route of exposure inhalative Concentration

mg/m³

Derived No Effect Level (DNEL) Type of value

Reference group Consumer Route of exposure oral

2.5 Concentration mg/kg

Propylidynetrimethanol, ethoxylated, esters with acrylic acid

Type of value Derived No Effect Level (DNEL)

Reference group Worker Long term Duration of exposure Route of exposure inhalative Mode of action Systemic effects

Concentration mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group Worker Duration of exposure Long term Route of exposure dermal

Mode of action Systemic effects

Concentration 10.5 mg/kg

Predicted No Effect Concentration (PNEC)

Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide

PNEC Type of value Type Saltwater

Concentration 0,00014 mg/l

Type of value

Type Freshwater sediment

Concentration 0,115 mg/kg

Type of value **PNEC**

Type Marine sediment

Concentration 0,0115 mg/kg

PNEC Type of value

Type Soil

Concentration 0,0222 mg/kg



Trade name: FotoTec Repair opaque

Substance number: 71028 Version: 1 / GB Date revised: 14.03.2023

Replaces Version: -/GB Print date: 14.03.2023

2-hydroxyethyl methacrylate

Type of value PNEC Freshwater

Concentration 0,482 mg/l

Type of value PNEC Type Soil

Concentration 0,476 mg/kg

Type of value PNEC

Type Sewage treatment plant (STP)

Concentration 10 mg/l

Type of value PNEC

Type Freshwater sediment

Concentration 3,79 mg/kg

Type of value PNEC Saltwater

Concentration 0,482 mg/l

Type of value PNEC

Type Marine sediment

Concentration 3,79 mg/kg

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters

with acrylic acid

Type of value PNEC
Type Freshwater

Concentration 0,1 mg/l

Type of value PNEC Saltwater

Concentration 0,01 mg/l

Type of value PNEC

Type Freshwater sediment

Concentration 35,8 mg/kg

Type of value PNEC

Type Marine sediment

Concentration 3,58 mg/kg

Type of value PNEC Type Soil

Concentration 71 mg/kg

Type of value PNEC

Type Sewage treatment plant (STP)

Concentration 10 mg/l

Hydroxylpropyl methacrylate

Reference substance Hydroxylpropyl methacrylate

Type of value PNEC
Type Freshwater



Print date: 14.03.2023

mg/l

Trade name: FotoTec Repair opaque

Substance number: 71028 Version: 1 / GB Date revised: 14.03.2023

Replaces Version: -/GB

Concentration 0,904 mg/l

Hydroxylpropyl methacrylate

Type of value PNEC

Type Freshwater sediment

Concentration 6,28 mg/kg

Hydroxylpropyl methacrylate

Type of value PNEC Type Soil

Concentration 0,727 mg/kg

Hydroxylpropyl methacrylate

Type of value PNEC

Type Sewage treatment plant (STP)

Concentration 10 mg/l

Type of value PNEC Type Marine

Concentration 0,904 mg/l

Type of value PNEC

Type Marine sediment

Concentration 6,28 mg/kg

Propylidynetrimethanol, ethoxylated, esters with acrylic acid

Type of value PNEC
Type Freshwater
Concentration 0,002

Type of value PNEC

Type Saltwater
Concentration 0,0002

Concentration 0,0002 mg/l

Type of value PNEC

Type Sewage treatment plant (STP)

Concentration 10 mg/l

Type of value PNEC

Type Freshwater sediment

Concentration 0,038 mg/kg/d

Type of value PNEC

Type Marine sediment

Concentration 0,004 mg/kg/d

Type of value PNEC Type Soil

Concentration 0,006 mg/kg/d

Type of value PNEC

Type Water (intermittent release)

Concentration 0,019 mg/l

8.2. Exposure controls



Trade name: FotoTec Repair opaque

Substance number: 71028 Version: 1 / GB Date revised: 14.03.2023

Replaces Version: -/GB Print date: 14.03.2023

General protective and hygiene measures

Do not smoke during work time. Hold emergency shower available. Hold eye wash fountain available. Do not inhale gases/vapours/aerosols. Avoid contact with skin and eyes. Take off immediately all contaminated clothing. Do not eat or drink during work time. Storage of foodstuffs in work rooms is forbidden. Wash hands before breaks and after work. Clean skin thoroughly after work; apply skin cream.

Respiratory protection

Do not inhale vapours; Use suitable respiratory protective device in case of insufficient ventilation

Hand protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Hand protection must comply with EN 374. Appropriate Material Butyl rubber

Eye protection

Safety glasses

Body protection

Clothing as usual in the chemical industry.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state liquid, viscous

Colour beige

Odour characteristic

Melting point

Remarks not determined

Freezing point

Remarks not determined

Boiling point or initial boiling point and boiling range

Value > 100 °C

Flammability

not determined

Upper and lower explosive limits

Remarks not determined

Flash point

Value 209 °C

Method closed cup

Ignition temperature

Remarks not determined

Decomposition temperature

Remarks not determined

pH value

Remarks not determined



Trade name: FotoTec Repair opaque

Substance number: 71028 Version: 1 / GB Date revised: 14.03.2023

Replaces Version: -/GB Print date: 14.03.2023

Viscosity

Remarks not determined

Solubility(ies)

Remarks not determined

Partition coefficient n-octanol/water (log value)

Remarks not determined

Vapour pressure

Remarks not determined

Density and/or relative density

Value 1,14 g/cm³

Temperature 20 °C

Relative vapour density

Remarks not determined

9.2. Other information

Odour threshold

Remarks not determined

Evaporation rate (ether = 1):

Remarks not determined

Solubility in water

Remarks virtually insoluble

Explosive properties

evaluation not determined

Oxidising properties

Remarks not determined

Other information

None known

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reactions when stored and handled according to prescribed instructions.

10.2. Chemical stability

No hazardous reactions known.

10.3. Possibility of hazardous reactions

No hazardous reactions known.

10.4. Conditions to avoid

Protect from heat and direct sunlight

10.5. Incompatible materials

None known

10.6. Hazardous decomposition products

Toxic gases/vapours, Irritant gases/vapours



Trade name: FotoTec Repair opaque

Substance number: 71028 Version: 1 / GB Date revised: 14.03.2023

Replaces Version: -/GB Print date: 14.03.2023

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity

ATE 5.300,60 mg/kg

12

Method calculated value (Regulation (EC) No. 1272/2008)

Acute oral toxicity (Components)

Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide

Species rat

LD50 > 5000 mg/kg

Method OECD 401

2-hydroxyethyl methacrylate

Species rat

LD50 > 5564 mg/kg

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters

with acrylic acid

Species Rats (male/female)

LD50 > 2000 mg/kg

Method OECD 401

Hydroxylpropyl methacrylate

Species rat

LD50 >= 2000 mg/kg

Method OECD 401

Propylidynetrimethanol, ethoxylated, esters with acrylic acid

Species rat

LD50 > 2000 mg/kg

Method OECD 401

Aliphatic urethane methacrylate

Species rat

LD50 > 2000 mg/kg

Acute dermal toxicity

Remarks Based on available data, the classification criteria are not met.

Acute dermal toxicity (Components)

Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide

Species rat

LD50 > 2000 mg/kg

Method OECD 402

2-hydroxyethyl methacrylate

Species rabbit

LD50 5000 mg/kg
Remarks Test conducted with a similar formulation.

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters

with acrylic acid

Species Rats (male/female)

LD50 > 2000 mg/kg

Method OECD 402

Hydroxylpropyl methacrylate

Species rabbit

LD50 > 5000 mg/kg



Trade name: FotoTec Repair opaque

Substance number: 71028 Version: 1 / GB Date revised: 14.03.2023

Replaces Version: -/GB Print date: 14.03.2023

Propylidynetrimethanol, ethoxylated, esters with acrylic acid

Species rabbit

LD50 > 13200 mg/kg

Aliphatic urethane methacrylate

Species rabbit

LD50 > 2000 mg/kg

Acute inhalational toxicity

ATE 6,1827 mg/l

Administration/Form Dust/Mist

Method calculated value (Regulation (EC) No. 1272/2008)

Remarks Based on available data, the classification criteria are not met.

Acute inhalative toxicity (Components)

Aliphatic urethane methacrylate

Remarks Based on available data, the classification criteria are not met.

Skin corrosion/irritation

evaluation irritant

Remarks The classification criteria are met.

Skin corrosion/irritation (Components)

Aliphatic urethane methacrylate

Remarks Based on available data, the classification criteria are not met.

Serious eye damage/irritation

evaluation irritant

Remarks The classification criteria are met.

Serious eye damage/irritation (Components)

2-hydroxyethyl methacrylate

Species rabbit

evaluation slightly irritant

Hydroxylpropyl methacrylate

Species rabbit evaluation slightly irritant

Propylidynetrimethanol, ethoxylated, esters with acrylic acid

Species rabbit evaluation irritant Method OECD 405

Aliphatic urethane methacrylate

Species rabbit evaluation irritant

Sensitization

evaluation May cause sensitization by skin contact. Remarks The classification criteria are met.

Sensitization (Components)

Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide

Route of exposure dermal Species mouse

evaluation May cause sensitization by skin contact.

2-hydroxyethyl methacrylate

Remarks Possible sensitization potential with human beings.

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters

with acrylic acid

Route of exposure dermal



Trade name: FotoTec Repair opaque

Substance number: 71028 Version: 1 / GB Date revised: 14.03.2023

Replaces Version: -/GB Print date: 14.03.2023

Species mouse evaluation sensitizing Method OECD 429

Hydroxylpropyl methacrylate

Species mouse

evaluation non-sensitizing
Method OECD 429

Remarks May cause sensitization by skin contact.

Propylidynetrimethanol, ethoxylated, esters with acrylic acid

Route of exposure dermal guinea pig evaluation sensitizing Method OECD 406

Aliphatic urethane methacrylate

Remarks Based on available data, the classification criteria are not met.

Subacute, subchronic, chronic toxicity

Remarks not determined

Mutagenicity

Remarks Based on available data, the classification criteria are not met.

Mutagenicity (Components)

Aliphatic urethane methacrylate

evaluation Based on available data, the classification criteria are not met.

Reproductive toxicity

Remarks Based on available data, the classification criteria are not met.

Reproduction toxicity (Components)

Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide

evaluation Suspected of damaging fertility.

Aliphatic urethane methacrylate

Remarks Based on available data, the classification criteria are not met.

Carcinogenicity

Remarks Based on available data, the classification criteria are not met.

Carcinogenicity (Components)

Aliphatic urethane methacrylate

evaluation Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity (STOT)

Single exposure

Remarks Based on available data, the classification criteria are not met.

Repeated exposure

Remarks Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity (STOT) (Components)

Aliphatic urethane methacrylate

Remarks Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties with respect to humans

The product does not contain a substance that has endocrine disrupting properties with respect to



Trade name: FotoTec Repair opaque

Substance number: 71028 Version: 1/GB Date revised: 14.03.2023

> Replaces Version: -/GB Print date: 14.03.2023

humans.

Experience in practice

Inhalation may lead to irritation of the respiratory tract.

Other information

No toxicological data are available.

SECTION 12: Ecological information

12.1. Toxicity

General information

not determined

Fish toxicity (Components)

Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide

Species carp (Cyprinus carpio)

LC50 1,4 mg/l

Duration of exposure 96 h

Method **OECD 203**

2-hydroxyethyl methacrylate

Species Oryzias latipes

LC50 100 mg/l

Duration of exposure 96 h

OECD 203 Method

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid

Species carp (Cyprinus carpio)

LC50 100 mg/l

Duration of exposure 96 h

ISO 7346 Method

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid

Species Fathead minnow (Pimephales promelas)

NOEC 0,25 mg/l

33 Duration of exposure d **OECD 210**

Method

Hydroxylpropyl methacrylate

Species golden orfe (Leuciscus idus)

LC50 493 mg/l

Duration of exposure 48 DIN 38412 / Part 15 Method

Propylidynetrimethanol, ethoxylated, esters with acrylic acid

Species Zebrabaerbling

LC50 1,95 mg/l

Duration of exposure 96 h

OECD 203 Method

Daphnia toxicity (Components)

Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide

Species Daphnia magna

EC50 3,53 mg/l

Duration of exposure 48 h

Method **OECD 202**



Print date: 14.03.2023

Trade name: FotoTec Repair opaque

Substance number: 71028 Version: 1 / GB Date revised: 14.03.2023

Replaces Version: -/GB

2-hydroxyethyl methacrylate

Species Daphnia magna

EC50 380 mg/l

Duration of exposure 48 h

Method OECD 202

2-hydroxyethyl methacrylate

Species Daphnia magna

NOEC 24,1 mg/l

Duration of exposure 21 d

Method OECD 211

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters

with acrylic acid

Species Daphnia magna

EC50 > 100 mg/l

Duration of exposure 48 h

Method OECD 202

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters

with acrylic acid

Species Daphnia magna

NOEC >= 0,51 mg/l

Duration of exposure 21 d

Method OECD 211

Hydroxylpropyl methacrylate

Species Daphnia magna

EC50 > 143 mg/l

Duration of exposure 48 h

Method OECD 202

Hydroxylpropyl methacrylate

Species Daphnia magna

NOEC 45,2 mg/l

Duration of exposure 21 d

Method OECD 211

Propylidynetrimethanol, ethoxylated, esters with acrylic acid

Species Daphnia magna

EC50 70,7 mg/l

Duration of exposure 48 h

Method OECD 202

Algae toxicity (Components)

Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide

Species Pseudokirchneriella subcapitata

EC50 > 2,01 mg/l

Duration of exposure 72 h

Method OECD 201

2-hydroxyethyl methacrylate

Species Pseudokirchneriella subcapitata

EC50 836 mg/l

Duration of exposure 72 h

Method OECD 201

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters

with acrylic acid

Species Pseudokirchneriella subcapitata

ErC50 105 mg/l

Duration of exposure 72 h

Method OECD 201



Print date: 14.03.2023

Trade name: FotoTec Repair opaque

Substance number: 71028 Version: 1 / GB Date revised: 14.03.2023

Replaces Version: -/GB

Hydroxylpropyl methacrylate

Species Pseudokirchneriella subcapitata

EC50 > 97,2 mg/l

Duration of exposure 72 h

Method OECD 201

Propylidynetrimethanol, ethoxylated, esters with acrylic acid

Species Scenedesmus subspicatus

EC50 2,2 mg/l

Duration of exposure 72 h

Method OECD 201

Bacteria toxicity (Components)

Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide

Species activated sludge

EC50 > 1000 mg/l

Duration of exposure 3 h

Method OECD 209

2-hydroxyethyl methacrylate

Species Pseudomonas fluorescens

EC0 > 3000 mg/l

Duration of exposure 16 h

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters

h

with acrylic acid

Species activated sludge

EC50 > 1000 mg/l

Duration of exposure 3 h

Method OECD 209

Propylidynetrimethanol, ethoxylated, esters with acrylic acid

Species activated sludge

EC20 292 mg/l

Duration of exposure 3

Method OECD 209

12.2. Persistence and degradability

General information

not determined

Biodegradability (Components)

Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide

Value < 0 to 10 %

Duration of test 28 d evaluation not readily degradable

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters

with acrylic acid

Value 42 %
Duration of test 28 d

evaluation biodegradable

Ready degradability (Components)

2-hydroxyethyl methacrylate

Value 92 to 100 %

Duration of test 14 d

Method Sewage water systeme

Hydroxylpropyl methacrylate

Value 81 %



Trade name: FotoTec Repair opaque

Substance number: 71028 Version: 1 / GB Date revised: 14.03.2023

Replaces Version: -/GB Print date: 14.03.2023

Duration of test 28 Days

Propylidynetrimethanol, ethoxylated, esters with acrylic acid

Value 58 to 61 %

Duration of test 28 d

12.3. Bioaccumulative potential

General information

not determined

Partition coefficient n-octanol/water (log value)

Remarks not determined

Octanol/water partition coefficient (log Pow) (Components)

Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide

log Pow 3,1

Temperature 23 °C

2-hydroxyethyl methacrylate

log Pow 0,42

Temperature 25 °C

Method OECD 107

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters

with acrylic acid

log Pow < 1,6 to 3,8

Hydroxylpropyl methacrylate

log Pow 0,97

Temperature 20 °C

Propylidynetrimethanol, ethoxylated, esters with acrylic acid

log Pow 2,89

Temperature 23 °C

Method OECD 107

Bioconcentration factor (BCF) (Components)

Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide

BCF 47 to 55

Concentration 0,1 mg/l
Duration of exposure 8 Weeks
Medium Freshwater

Species carp (Cyprinus carpio)

12.4. Mobility in soil

General information

not determined

12.5. Results of PBT and vPvB assessment

General information

not determined

Results of PBT and vPvB assessment

The product contains no PBT substances

The product contains no vPvB substances.

12.6 Endocrine disrupting properties

Endocrine disrupting properties with respect to the envrionment

The product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms.



Trade name: FotoTec Repair opaque

Substance number: 71028 Version: 1 / GB Date revised: 14.03.2023

Replaces Version: -/GB Print date: 14.03.2023

12.7. Other adverse effects

General information

not determined

General information / ecology

Do not allow to enter soil, waterways or waste water canal. Avoid release into the atmosphere.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations for the product

Must not be disposed together with household garbage. Dispose of waste according to applicable legislation.

Disposal recommendations for packaging

Packaging that cannot be cleaned should be disposed off as product waste.

SECTION 14: Transport information

	Land transport ADR/RID	Marine transport IMDG/GGVSee	Air transport ICAO/IATA
14.1. UN number	The product does not constitute a hazardous substance in land transport.	The product does not constitute a hazardous substance in sea transport.	The product does not constitute a hazardous substance in air transport.
14.2. UN proper shipping name	-	-	-
14.3. Transport hazard class(es)		-	-
Label			
14.4. Packing group		-	-
14.5. Environmental hazards		no	
	-		-

SECTION 15: Regulatory information

15.2. Chemical safety assessment

For this preparation a chemical safety assessment has not been carried out.

SECTION 16: Other information

Hazard statements listed in Chapter 3



Trade name: FotoTec Repair opaque

Substance number: 71028 Version: 1 / GB Date revised: 14.03.2023

Replaces Version: -/GB Print date: 14.03.2023

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H361f Suspected of damaging fertility.

H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

CLP categories listed in Chapter 3

Aquatic Chronic 2 Hazardous to the aquatic environment, chronic, Category 2 Hazardous to the aquatic environment, chronic, Category 3

Eye Irrit. 2 Eye irritation, Category 2

Repr. 2 Reproductive toxicity, Category 2
Skin Irrit. 2 Skin irritation, Category 2
Skin Sens. 1 Skin sensitization, Category 1
Skin Sens. 1B Skin sensitization, Category 1B

Supplemental information

Relevant changes compared with the previous version of the safety data sheet are marked with: *** This information is based on our present state of knowledge. However, it should not constitute a guarantee for any specific product properties and shall not establish a legally valid relationship.