

Trade name: FotoTec SL.A opaque

Substance number: S0024 Version: 1 / GB Date revised: 26.07.2023

Replaces Version: - / GB Print date: 26.07.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

FotoTec SL.A opaque

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/preparation

Light-curing material for the production of earmolds by means of 3D printing processes

1.3. Details of the supplier of the safety data sheet

Address/Manufacturer

Dreve Otoplastik GmbH Max-Planck-Straße 31

59423 Unna

Telephone no. +49 2303 8807-0 Fax no. +49 2303 8807-29

Information provided Department Research & Development: Fax: +49 2303 8807-562

by / telephone

E-mail address of sicherheitsdatenblatt@dreve.de

person responsible for this SDS

1.4. Emergency telephone number

Henkel Fire Department / 24h-Emergency-Contact-No.: +49 211 797-3350

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (Regulation (EC) No. 1272/2008)

Classification (Regulation (EC) No. 1272/2008)

Skin Sens. 1A H317 Aquatic Chronic 3 H412

The product is classified and labelled in accordance with Regulation (EC) No 1272/2008 For explanation of abbreviations see section 16.

2.2. Label elements

Labelling according to regulation (EC) No 1272/2008

Hazard pictograms



Signal word

Warning

Hazard statements



Trade name: FotoTec SL.A opaque

Substance number: S0024 Version: 1 / GB Date revised: 26.07.2023

Replaces Version: - / GB Print date: 26.07.2023

%

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P501.1 Dispose of contents/container to industrial incineration plant.

Hazardous component(s) to be indicated on label (Regulation (EC) No. 1272/2008)

contains Tetramethylene dimethacrylate; 7,7,9(7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-

5,12-diazahexadecane-1,16-diylbismethacrylate; Phenyl bis(2,4,6-

trimethylbenzoyl)-phosphine oxide

2.3. Other hazards

No special hazards have to be mentioned.

The product contains no PBT substances. The product contains no vPvB substances. This product does not contain a substance that has endocrine disrupting properties with respect to human. The product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients

Bisphenol A, ethoxylated, dimethacrylate

CAS No. 41637-38-1 EINECS no. 609-946-4

Registration no. 01-2119980659-17 Concentration >= 50

Classification (Regulation (EC) No. 1272/2008)

Aquatic Chronic 4 H413

7,7,9(7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diylbismethacrylate

CAS No. 72869-86-4 EINECS no. 276-957-5

Registration no. 01-2120751202-68

Concentration >= 10 < 25 %

Classification (Regulation (EC) No. 1272/2008)

Skin Sens. 1B H317 Aquatic Chronic 2 H411

Tetramethylene dimethacrylate

CAS No. 2082-81-7 EINECS no. 218-218-1

Registration no. 01-2119967415-30

Concentration >= 1 < 10 %

Classification (Regulation (EC) No. 1272/2008)

Skin Sens. 1B H317

Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide



Trade name: FotoTec SL.A opaque

Substance number: S0024 Version: 1 / GB Date revised: 26.07.2023

Replaces Version: - / GB Print date: 26.07.2023

CAS No. 162881-26-7 EINECS no. 423-340-5

Registration no. 01-2119489401-38

Concentration >= 1 < 10 %

Classification (Regulation (EC) No. 1272/2008)

Skin Sens. 1A H317 Aquatic Chronic 4 H413

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated clothing immediately and dispose of safely. Adhere to personal protective measures when giving first aid

After inhalation

Remove the casualty into fresh air and keep him calm. In the event of symptoms take medical treatment.

After skin contact

After contact with skin, wash immediately with plenty of water and soap. Consult a doctor if skin irritation persists.

After eye contact

Separate eyelids, wash the eyes thoroughly with water (15 min.). Take medical treatment.

After ingestion

Call in a physician immediately and show him the Safety Data Sheet. Rinse mouth thoroughly with water. Let plenty of water be drunk in small gulps. Do not induce vomiting.

Adhere to personal protective measures when giving first aid

First aider: Pay attention to self-protection!

4.2. Most important symptoms and effects, both acute and delayed

Until now no symptoms known so far.

4.3. Indication of any immediate medical attention and special treatment needed Hints for the physician / hazards

In the case of swallowing with subsequent vomiting, aspiration of the lungs can occur which can lead to chemical pneumonia or asphyxiation.

or aspriyation.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Recommended: alcohol resistant foam, CO2, powders, water spray/mist, Extinguishing measures to suit surroundings

Non suitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

In case of combustion evolution of dangerous gases possible.



Trade name: FotoTec SL.A opaque

Substance number: S0024 Version: 1 / GB Date revised: 26.07.2023

Replaces Version: - / GB Print date: 26.07.2023

5.3. Advice for firefighters

Special protective equipment for fire-fighting

Do not inhale explosion and/or combustion gases. In case of combustion use a suitable breathing apparatus. Wear full protective suit.

Other information

Collect contaminated fire-fighting water separately, must not be discharged into the drains. Fire residues and contaminated fire-fighting water must be disposed of in accordance with the local regulations. Observe manufacturer's / distributor`s instructions.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away sources of ignition. Ensure adequate ventilation. Use breathing apparatus if exposed to vapours/dust/aerosol. Avoid contact with skin, eyes and clothing. Use personal protective clothing. Refer to protective measures listed in Sections 7 and 8.

6.2. Environmental precautions

Prevent spread over a wide area (e.g. by containment or oil barriers). Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil. Retain and dispose of contaminated wash water. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Pick up rest with suitable absorbent materials. Do not pick up with the help of saw-dust or other combustible substances. Clean contaminated floors and objects thoroughly, observing environmental regulations. Containers in which spilt substance has been collected must be adequately labelled. Dispose of as prescribed.

6.4. Reference to other sections

Refer to protective measures listed in Sections 7 and 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Provide good ventilation of working area (local exhaust ventilation if necessary). Avoid formation of aerosols. Avoid impact, friction and electro-static loading; risk of ignition!. Keep container tightly closed.

Advice on protection against fire and explosion

Keep away from sources of heat and ignition. No smoking. Take action to prevent static discharges. Avoid impact and friction. Use only explosion-proof equipment. Keep away from combustible material. Wear shoes with conductive soles.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep in original packaging, tightly closed. Storage rooms must be properly ventilated. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Hints on storage assembly

Do not store together with foodstuffs. Do not store with strong oxidizing agents.

Further information on storage conditions



Trade name: FotoTec SL.A opaque

Substance number: S0024 Version: 1 / GB Date revised: 26.07.2023

Replaces Version: - / GB Print date: 26.07.2023

Keep under lock and key or accessible only to specialists or people who are authorized. Keep container tightly closed and in a well-ventilated place. Keep in a cool place

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Other information

Contains no substances with occupational exposure limit values.

Derived No/Minimal Effect Levels (DNEL/DMEL)

Tetramethylene dimethacrylate

Type of value Derived No Effect Level (DNEL)

Reference group Worker
Duration of exposure Long term
Route of exposure inhalative
Mode of action Systemic effects

Concentration 14,5 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group Worker
Duration of exposure Long term
Route of exposure dermal

Mode of action Systemic effects

Concentration 4,2 mg/kg/d

Type of value Derived No Effect Level (DNEL)

Reference group Consumer

Duration of exposure Long term

Route of exposure inhalative

Mode of action Systemic effects

Concentration 4,3 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group Consumer
Duration of exposure Long term
Route of exposure oral

Mode of action Systemic effects

Concentration 2,5 mg/kg

Type of value Derived No Effect Level (DNEL)

Reference group Consumer
Duration of exposure Long term
Route of exposure dermal

Mode of action Systemic effects

Concentration 2,5 mg/kg

Bisphenol A, ethoxylated, dimethacrylate

Type of value Derived No Effect Level (DNEL)

Reference group

Duration of exposure

Route of exposure

Mode of action

Worker

Long term

inhalative

Systemic effects

Concentration 3,52 mg/m³



Trade name: FotoTec SL.A opaque

Substance number: S0024 Version: 1 / GB Date revised: 26.07.2023

Replaces Version: - / GB Print date: 26.07.2023

Type of value Derived No Effect Level (DNEL)

Reference group Worker
Duration of exposure Long term
Route of exposure dermal

Mode of action Systemic effects

Concentration 2 mg/kg

Type of value Derived No Effect Level (DNEL)

Reference group

Duration of exposure

Route of exposure

Mode of action

Consumer

Long term

inhalative

Systemic effects

Concentration 0,87 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group Consumer
Duration of exposure Long term
Route of exposure dermal

Mode of action Systemic effects

Concentration 1 mg/kg

Type of value Derived No Effect Level (DNEL)

Reference group Consumer
Duration of exposure Long term
Route of exposure oral

Mode of action Systemic effects

Concentration 0,5 mg/kg

7,7,9(7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diylbismethacrylate

Type of value Derived No Effect Level (DNEL)

Reference group Worker
Duration of exposure Long term
Route of exposure inhalative
Mode of action Systemic effects

Concentration 3,3 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group Worker
Duration of exposure Long term
Route of exposure dermal

Mode of action Systemic effects

Concentration 1,3 mg/kg

Type of value Derived No Effect Level (DNEL)

Reference group Consumer

Duration of exposure Long term

Route of exposure inhalative

Mode of action Systemic effects

Concentration 0,6 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group Consumer

Duration of exposure Long term

Route of exposure oral

Mode of action Systemic effects

Concentration 0,3 mg/kg



Print date: 26.07.2023

Trade name: FotoTec SL.A opaque

Substance number: S0024 Version: 1 / GB Date revised: 26.07.2023

Replaces Version: - / GB

Type of value Derived No Effect Level (DNEL)

Reference group Consumer
Duration of exposure Long term
Route of exposure dermal

Mode of action Systemic effects

Concentration 0,7 mg/kg

Predicted No Effect Concentration (PNEC)

Tetramethylene dimethacrylate

Type of value PNEC
Type Freshwater

Concentration 0,043 mg/l

Type of value PNEC
Type Saltwater

Concentration 0,004 mg/l

Type of value PNEC

Type Water (intermittent release)

Concentration 0,098 mg/l

Type of value PNEC

Type Sewage treatment plant (STP)

Concentration 2 mg/l

Type of value PNEC

Type Freshwater sediment

Concentration 3,12 mg/kg

Type of value PNEC

Type Marine sediment

Concentration 0,312 mg/kg

Type of value PNEC Type Soil

Concentration 0,573 mg/kg

7,7,9(7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diylbismethacrylate

Type of value PNEC
Type Freshwater

Concentration 0,01 mg/l

Type of value PNEC

Type Freshwater sediment

Concentration 4,56 mg/kg

Type of value PNEC Saltwater

Concentration 0,001 mg/l

Type of value PNEC

Type Marine sediment

Concentration 0,46 mg/kg

Type of value PNEC



Trade name: FotoTec SL.A opaque

Substance number: S0024 Version: 1 / GB Date revised: 26.07.2023

Replaces Version: - / GB Print date: 26.07.2023

Type Soil

Concentration 0,91 mg/kg

Type of value PNEC

Type Sewage treatment plant (STP)

Concentration 3,61 mg/l

Type of value PNEC

Type Water (intermittent release)

Concentration 0,1 mg/l

8.2. Exposure controls

General protective and hygiene measures

Do not smoke during work time. Hold emergency shower available. Hold eye wash fountain available. Do not inhale gases/vapours/aerosols. Avoid contact with skin and eyes. Take off immediately all contaminated clothing. Do not eat or drink during work time. Storage of foodstuffs in work rooms is forbidden. Wash hands before breaks and after work. Clean skin thoroughly after work; apply skin cream.

Respiratory protection

Do not inhale vapours; Use suitable respiratory protective device in case of insufficient ventilation

Hand protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Hand protection must comply with EN 374.

Appropriate Material nitrile

Eye protection

Safety glasses

Body protection

Clothing as usual in the chemical industry.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state
Colour
Ddour

liquid
beige
characteristic

Melting point

Remarks not determined

Freezing point

Remarks not determined

Boiling point or initial boiling point and boiling range

Value < 114 °C

Flammability

evaluation not determined

Upper and lower explosive limits



Trade name: FotoTec SL.A opaque

Substance number: S0024 Version: 1 / GB Date revised: 26.07.2023

Replaces Version: - / GB Print date: 26.07.2023

Remarks not determined

Flash point

Value > 100 °C Method closed cup

Ignition temperature

Remarks not determined

Decomposition temperature

Remarks not determined

pH value

Remarks not determined

Viscosity

Remarks not determined

Solubility(ies)

Remarks not determined

Partition coefficient n-octanol/water (log value)

Remarks not determined

Vapour pressure

Remarks not determined

Density and/or relative density

Value 1,12 g/cm³

Temperature 20 °C

Relative vapour density

Remarks not determined

9.2. Other information

Odour threshold

Remarks not determined

Evaporation rate (ether = 1):

Remarks not determined

Solubility in water

Remarks virtually insoluble

Explosive properties

evaluation not determined

Oxidising properties

Remarks not determined

Other information

None known

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reactions when stored and handled according to prescribed instructions.

10.2. Chemical stability

No hazardous reactions known.

10.3. Possibility of hazardous reactions



Trade name: FotoTec SL.A opaque

Substance number: S0024 Version: 1 / GB Date revised: 26.07.2023

Replaces Version: - / GB Print date: 26.07.2023

No hazardous reactions known.

10.4. Conditions to avoid

Protect from heat and direct sunlight

10.5. Incompatible materials

None known

10.6. Hazardous decomposition products

Irritant gases/vapours

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity

Remarks Based on available data, the classification criteria are not met.

Acute oral toxicity (Components)

Tetramethylene dimethacrylate

Species rat

LD50 10066 mg/kg

Method OECD 401

Bisphenol A, ethoxylated, dimethacrylate

Species rat

LD50 > 2000 mg/kg Remarks Test conducted with a similar formulation.

7,7,9(7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diylbismethacrylate

Species rat

LD50 > 5000 mg/kg

Method OECD 401

Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide

Species rat

LD50 > 2000 mg/kg

Method OECD 401

Acute dermal toxicity

Remarks Based on available data, the classification criteria are not met.

Acute dermal toxicity (Components)

Bisphenol A, ethoxylated, dimethacrylate

Species rat

LD50 > 2000 mg/kg

Method OECD 402

Remarks Test conducted with a similar formulation.

7,7,9(7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diylbismethacrylate

Species rat

LD50 > 2000 mg/kg

Method OECD 402

Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide

Species rat

LD50 > 2000 mg/kg

Method OECD 402

Acute inhalational toxicity



Trade name: FotoTec SL.A opaque

Substance number: S0024 Version: 1 / GB Date revised: 26.07.2023

Replaces Version: - / GB Print date: 26.07.2023

ATE > 20 mg/l

Administration/Form Dust/Mist

Method calculated value (Regulation (EC) No. 1272/2008)

Remarks Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Remarks Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Remarks Based on available data, the classification criteria are not met.

Sensitization

evaluation May cause sensitization by skin contact. Remarks The classification criteria are met.

Sensitization (Components)

Tetramethylene dimethacrylate

Route of exposure dermal species mouse evaluation sensitizing Method OECD 429

7,7,9(7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diylbismethacrylate

Route of exposure dermal Species mouse evaluation sensitizing

Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide

Route of exposure dermal guinea pig evaluation sensitizing Method OECD 406

Subacute, subchronic, chronic toxicity

Remarks not determined

Mutagenicity

Remarks Based on available data, the classification criteria are not met.

Reproductive toxicity

Remarks Based on available data, the classification criteria are not met.

Carcinogenicity

Remarks Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity (STOT)

Single exposure

Remarks Based on available data, the classification criteria are not met.

Repeated exposure

Remarks Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties with respect to humans

The product does not contain a substance that has endocrine disrupting properties with respect to humans.

Experience in practice

Inhalation may lead to irritation of the respiratory tract.



Trade name: FotoTec SL.A opaque

Substance number: S0024 Version: 1 / GB Date revised: 26.07.2023

Replaces Version: - / GB Print date: 26.07.2023

Other information

No toxicological data are available.

SECTION 12: Ecological information

12.1. Toxicity

General information

not determined

Fish toxicity (Components)

Tetramethylene dimethacrylate

Species golden orfe (Leuciscus idus)

LC50 32,5 mg/l

Duration of exposure 48 h Method DIN 38412 / Part 15

Remarks Test conducted with a similar formulation.

Bisphenol A, ethoxylated, dimethacrylate

Species rainbow trout (Oncorhynchus mykiss)

LL50 > 100 mg/l

Method OECD 203

Remarks Test conducted with a similar formulation.

7,7,9(7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diylbismethacrylate

Species zebra fish (Brachydanio rerio)

LC50 10,1 mg/l

Duration of exposure 96 h

Method OECD 203

Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide

Species zebra fish (Brachydanio rerio)

LC50 > 90 μg/l

Duration of exposure 96 h

Method OECD 203

Daphnia toxicity (Components)

Tetramethylene dimethacrylate

Species Daphnia magna

EC10 7,51 mg/l

Duration of exposure 21 d

Method OECD 211

Bisphenol A, ethoxylated, dimethacrylate

Species Daphnia magna

EL50 > 100 mg/l

Duration of exposure 48 h

Method OECD 202

7,7,9(7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diylbismethacrylate

Species Daphnia magna

EC50 1,2 mg/l

Duration of exposure 48

Method OECD 202

Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide

Species Daphnia magna

EC50 > 1175 μg/l

Duration of exposure 48 h

h



Trade name: FotoTec SL.A opaque

Substance number: S0024 Version: 1 / GB Date revised: 26.07.2023

Replaces Version: - / GB Print date: 26.07.2023

Method OECD 202

Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide

Species Daphnia magna

NOEC \Rightarrow 8,1 μ g/l

Duration of exposure 21 d

Method OECD 211

Algae toxicity (Components)

Tetramethylene dimethacrylate

Species Scenedesmus subspicatus

EC50 9,79 mg/l

Duration of exposure 72 h

Method OECD 201

Bisphenol A, ethoxylated, dimethacrylate

Species Pseudokirchneriella subcapitata

EL50 > 100 mg/l

Duration of exposure 72 h

Method OECD 201

Remarks Test conducted with a similar formulation.

7,7,9(7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diylbismethacrylate

Species Scenedesmus subspicatus

EC50 > 0,68 mg/l

Duration of exposure 72 h

Method OECD 201

Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide

Species Scenedesmus subspicatus

EC50 > 260 $\mu g/l$

Duration of exposure 72 h

Method OECD 201

Bacteria toxicity (Components)

Tetramethylene dimethacrylate

Species activated sludge

NOEC 20 mg/l

Duration of exposure 28 d

Bisphenol A, ethoxylated, dimethacrylate

Species activated sludge

NOEC 14,3 mg/l

Duration of exposure 28 d

Remarks Test conducted with a similar formulation.

7,7,9(7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diylbismethacrylate

Species activated sludge

NOEC >= 36,1 mg/l

Duration of exposure 14 d

Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide

Species activated sludge

EC50 > 100 mg/l

Duration of exposure 3 h

Method OECD 209

12.2. Persistence and degradability

General information

not determined

Biodegradability (Components)



Print date: 26.07.2023

Trade name: FotoTec SL.A opaque

Substance number: S0024 Version: 1 / GB Date revised: 26.07.2023

Replaces Version: - / GB

Tetramethylene dimethacrylate

Value 84 %

Duration of test 28 d

evaluation Readily biodegradable (according to OECD criteria)

Bisphenol A, ethoxylated, dimethacrylate

Value 24 %

Duration of test 28 d

evaluation Readily biodegradable (according to OECD criteria)

7,7,9(7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diylbismethacrylate

Value 22 %

Duration of test 28 d evaluation not readily degradable

Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide

Value 1 %

Duration of test 28 d evaluation not degradable

12.3. Bioaccumulative potential

General information

not determined

Partition coefficient n-octanol/water (log value)

Remarks not determined

Octanol/water partition coefficient (log Pow) (Components)

Tetramethylene dimethacrylate

log Pow 3,1

Temperature 20 °C

Bisphenol A, ethoxylated, dimethacrylate

log Pow 4 39

7,7,9(7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diylbismethacrylate

log Pow 3.39

Temperature 20 °C

Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide

log Pow 5,8

12.4. Mobility in soil

General information

not determined

12.5. Results of PBT and vPvB assessment

General information

not determined

Results of PBT and vPvB assessment

The product contains no PBT substances

The product contains no vPvB substances.

12.6 Endocrine disrupting properties

Endocrine disrupting properties with respect to the envrionment

The product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms.

12.7. Other adverse effects

General information



Trade name: FotoTec SL.A opaque

Substance number: S0024 Version: 1 / GB Date revised: 26.07.2023

Replaces Version: - / GB Print date: 26.07.2023

not determined

General information / ecology

Do not allow to enter soil, waterways or waste water canal. Avoid release into the atmosphere.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations for the product

Must not be disposed together with household garbage. Dispose of waste according to applicable legislation.

Disposal recommendations for packaging

Packaging that cannot be cleaned should be disposed off as product waste.

SECTION 14: Transport information

	Land transport ADR/RID	Marine transport IMDG/GGVSee	Air transport ICAO/IATA
14.1. UN number or ID number	The product does not constitute a hazardous substance in land transport.	The product does not constitute a hazardous substance in sea transport.	The product does not constitute a hazardous substance in air transport.
14.2. UN proper shipping name	-	-	-
14.3. Transport hazard class(es)		-	-
Label			
14.4. Packing group		<u>-</u>	-

SECTION 15: Regulatory information

15.2. Chemical safety assessment

For this preparation a chemical safety assessment has not been carried out.

SECTION 16: Other information

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification (Regulation (EC) No. 1272/2008)

Skin Sens. 1A H317 Calculation method Aquatic Chronic 3 H412 Calculation method

Hazard statements listed in Chapter 2/3

H317 May cause an allergic skin reaction.



Trade name: FotoTec SL.A opaque

Substance number: S0024 Version: 1 / GB Date revised: 26.07.2023

Replaces Version: - / GB Print date: 26.07.2023

H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.
 H413 May cause long lasting harmful effects to aquatic life.

CLP categories listed in Chapter 2/3

Aquatic Chronic 2 Hazardous to the aquatic environment, chronic, Category 2
Aquatic Chronic 3 Hazardous to the aquatic environment, chronic, Category 3
Aquatic Chronic 4 Hazardous to the aquatic environment, chronic, Category 4

Skin Sens. 1A Skin sensitization, Category 1A Skin Sens. 1B Skin sensitization, Category 1B

Supplemental information

Relevant changes compared with the previous version of the safety data sheet are marked with: *** This information is based on our present state of knowledge. However, it should not constitute a guarantee for any specific product properties and shall not establish a legally valid relationship.