Printing date 02.03.2023

Version number 5

Revision: 02.03.2023

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- · 1.1 Product identifier
- · Trade name: NanoScreen Soft Lack
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- Application of the substance / the mixture
 Silicone lacquer for coating earmolds and ear impressions
- 1.3 Details of the supplier of the safety data sheet
 Manufacturer/Supplier: Dreve Otoplastik GmbH Max-Planck-Straße 31
 59423 Unna / Germany Tel.: +49 2303 / 8807-0 Fax.: +49 2303 / 8807-29
- Further information obtainable from: Department Research & Development Fax: +49 2303 / 8807-562 Email: sicherheitsdatenblatt@dreve.de • 1.4 Emergency telephone number:
- Tel.: +49 211 / 797-3350 Plant Fire Department Henkel

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

GHS02 flame Flam. Liq. 2 H22

H225 Highly flammable liquid and vapour.

GHS08 health hazard

Repr. 2 H361d Suspected of damaging the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

GHS05 corrosion

GHS07

Eye Dam. 1H318Causes serious eye damage.

GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

Skin Irrit. 2 H315 Causes skin irritation.


GB



Printing date 02.03.2023

Version number 5

Revision: 02.03.2023



- **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

 Dangerous compor 	nents:	
CAS: 108-88-3 EINECS: 203-625-9	toluene	25-50%
	♦ Flam. Liq. 2, H225; ♦ Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304; ♦ Skin Irrit. 2, H315; STOT SE 3, H336	
CAS: 142-82-5	heptane	10-25%
EINECS: 205-563-8	♦ Flam. Liq. 2, H225; ♦ Asp. Tox. 1, H304; ♦ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ♦ Skin Irrit. 2, H315; STOT SE 3, H336	
	(Cont	d. on page 3)

GB -



Revision: 02.03.2023

Printing date 02.03.2023

Version number 5

Trade name: NanoScreen Soft Lack

CAS: 4253-34-3 methylsilanetriyl triacetate 2.5-10%

EINECS: 224-221-9 🔶 Skin Corr. 1B, H314

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:
- In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

• After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing:

Do not induce vomiting.

Call a doctor immediately.

- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- \cdot 5.2 Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- 5.3 Advice for firefighters
- Protective equipment: Mount respiratory protective device.

SECTION 6: Accidental release measures

 6.1 Personal precautions, protective equipment and emergency procedures Avoid contact with skin and eyes. Wear protective equipment. Keep unprotected persons away. · 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course. Prevent seepage into sewage system, workpits and cellars. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water. 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralising agent. Dispose contaminated material as waste according to item 13. Ensure adequate ventilation. 6.4 Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment.

(Contd. on page 4)

GB



Revision: 02.03.2023

(Contd. of page 3)

Printing date 02.03.2023

Version number 5

Trade name: NanoScreen Soft Lack

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Avoid contact with skin and eyes.
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
Information about fire - and explosion protection: Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.

Keep respiratory protective device available.

7.2 Conditions for safe storage, including any incompatibilities
Storage:
Requirements to be met by storerooms and receptacles: Protect from humidity and water.

Store in a cool location.

- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:
- Store in cool, dry conditions in well sealed receptacles.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

Acetic acid: MAK-Value: 25,0 mg/m³ bzw. 10 ppm

108-88-3 toluene

WEL Short-term value: 384 mg/m³, 100 ppm Long-term value: 191 mg/m³, 50 ppm Sk

142-82-5 heptane

WEL Long-term value: 2085 mg/m³, 500 ppm

• Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

Respiratory protection: Do not inhale fumes.

Use suitable respiratory protective device in case of insufficient ventilation.

(Contd. on page 5)

GB

Printing date 02.03.2023

Version number 5



Revision: 02.03.2023

Trade name: NanoScreen Soft Lack

(Contd. of page 4)

· Protection of hands:



Protective gloves

Protective gloves should be changed regularly, especially after intensive contact with the product. For every workplace a suitable type of protective gloves must be selected.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

Nitrile rubber, NBR

As there are many different conditions in every day work these indications can only serve as an aid to orientation for the selection of suitable gloves for the handling of chemical products. By no means they can replace qualifying examinations by the end-user.

These recommendations only apply to the product mentioned in the safety data sheet. When mixing with other substances or under conditions deviant from norm EN 374 a manufacturer of CE-approved gloves should be referred to.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

 9.1 Information on basic physical and chemical properties General Information 		
Appearance: Form:	Fluid	
Colour:	Colourless	
Odour:	Characteristic	
Odour threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition Melting point/freezing point: Initial boiling point and boiling	Undetermined. range: 98 °C	
Flash point:	-4 °C	
Flammability (solid, gas):	Not applicable.	



Printing date 02.03.2023

Version number 5

Revision: 02.03.2023

Trade name: NanoScreen Soft Lack

	(Contd. of page 5
· Ignition temperature:	>200 °C
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	1.1 Vol %
Upper:	7 Vol %
 Oxidising properties 	Not determined
 Vapour pressure at 20 °C: 	100 hPa
· Density at 20 °C:	0.84 g/cm ³
Relative density	Not determined.
· Vapour density	Not determined.
 Evaporation rate 	Not determined.
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic at 23 °C:	100 mPas
Kinematic:	Not determined.
 9.2 Other information 	No further relevant information available.

SECTION 10: Stability and reactivity

• 10.1 Reactivity No dangerous reactions if used according to specifications.

- 10.2 Chemical stability Stable if used according to specifications.
- Thermal decomposition / conditions to be avoided:
- Humidity

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions Formation of acetic acid by reactions with dampness.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: Dampness
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

108-8	108-88-3 toluene	
Oral	LD50	5,000 mg/kg (rat)
Derma	al LD50	12,124 mg/kg (rabbit)
Inhala	ative LC50/4 h	5,320 mg/l (mus)
•	•	(Contd. on page 7)

(Contd. on page 7)

GB



Printing date 02.03.2023 Ve

Version number 5

Revision: 02.03.2023

Trade name: NanoScreen Soft Lack

(Contd. of page 6)

- · Primary irritant effect:
- · Skin corrosion/irritation
- Causes skin irritation. • Serious eye damage/irritation Causes serious eye damage.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met. • Additional toxicological information:
- In contact with dampness product separates a small quantity of acetic acid, which irritates skin and mucous membranes.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity
- Suspected of damaging the unborn child.
- **STOT-single exposure** May cause drowsiness or dizziness.
- · STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

· Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system. Must not reach sewage water or drainage ditch undiluted or unneutralised. Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

- Toxic for aquatic organisms
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

· European waste catalogue	
HP 3	Flammable
HP 4	Irritant - skin irritation and eye damage
HP 5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

(Contd. on page 8)



Printing date 02.03.2023

Version number 5

Revision: 02.03.2023

Trade name: NanoScreen Soft Lack

	(Contd. of page 7)
HP 10	Toxic for reproduction
HP 14	Ecotoxic

Uncleaned packaging:
Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number ADR, IMDG, IATA	UN1993
14.2 UN proper shipping name ADR IMDG	1993 ENTZÜNDBARER FLÜSSIGER STOFF, N.A.G. (Dampfdruck bei 50°C höchstens 110 k P a) (T O L U E N , H E P T A N E) UMWELTGEFÄHRDEND FLAMMABLE LIQUID, N.O.S. (TOLUENE)
·IATA	HEPTANES), MARINE POLLUTANT FLAMMABLE LIQUID, N.O.S. (TOLUENE, HEPTANES)
• 14.3 Transport hazard class(es)	
· ADR, IMDG	
Class	3 Flammable liquids.
· Label	3
Class	3 Flammable liquids.
Label	3
· 14.4 Packing group · ADR, IMDG, IATA	II
· 14.5 Environmental hazards:	Product contains environmentally hazardous substances: heptane
· Marine pollutant:	Yes Symbol (fish and tree)
· Special marking (ADR):	Symbol (fish and tree)
 14.6 Special precautions for user Danger code (Kemler): EMS Number: 	Warning: Flammable liquids. 33 F-E, <u>S-E</u>
Stowage Category	В



Printing date 02.03.2023

Version number 5

Revision: 02.03.2023

Trade name: NanoScreen Soft Lack

	(Contd. of page 8
· Transport/Additional information:	
 ADR Limited quantities (LQ) Excepted quantities (EQ) 	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
 Transport category Tunnel restriction code 	2 D/E
 IMDG Limited quantities (LQ) Excepted quantities (EQ) 	1L Code: E2 Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 50 ml
· UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S (VAPOUR PRESSURE AT 50°C NOT MORI THAN 110 KPA) (TOLUENE, HEPTANES), 3, I ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category
- E2 Hazardous to the Aquatic Environment
- P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 48
- · National regulations:
- · Technical instructions (air):

Class	Share in %
NK	50-100

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H225 Highly flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H336 May cause drowsiness or dizziness.

(Contd. on page 10)



Printing date 02.03.2023

Version number 5

Revision: 02.03.2023

Trade name: NanoScreen Soft Lack

	(Contd. of page 9)
H361d Suspected of damaging the unborn child.	
H373 May cause damage to organs through prolonged or repeated exposure.	
H400 Very toxic to aquatic life.	
H410 Very toxic to aquatic life with long lasting effects.	
· Department issuing SDS: Department Research & Development	
Contact: Dr. Thomas Veit, Lothar Sutor	
· Abbreviations and acronyms:	
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreemen	t concerning the
International Carriage of Dangerous Goods by Road)	it concerning the
IMDG: International Maritime Code for Dangerous Goods	
IATA: International Air Transport Association	
GHS: Globally Harmonised System of Classification and Labelling of Chemicals	
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
Flam. Lig. 2: Flammable liquids – Category 2	
Skin Corr. 1B: Skin corrosion/irritation – Category 1B	
Skin Irrit. 2: Skin corrosion/irritation – Category 2	
Eye Dam. 1: Serious eye damage/eye irritation – Category 1	
Repr. 2: Reproductive toxicity – Category 2	
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3	
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1	
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1	
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1	
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2	
• * Data compared to the previous version altered.	
	GB —