Printing date 29.03.2022

Revision: 29.03.2022

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- · 1.1 Product identifier
- · Trade name: Thermosoft Lack
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- Application of the substance / the mixture Light-curing lacquer for earmolds
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier: Dreve Otoplastik GmbH Max-Planck-Straße 31 59423 Unna / Germany Tel.: +49 2303 / 8807-0 Fax.: +49 2303 / 8807-29
- Further information obtainable from: Department Research & Development Fax: +49 2303 / 8807-562 Email: sicherheitsdatenblatt@dreve.de
- **1.4 Emergency telephone number:** Tel.: +49 211 / 797-3350 Plant Fire Department Henkel

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture
 Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 2 H225 Highly flammable liquid and vapour.

GHS07

Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2 H319 Causes serious eye irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.
STOT SE 3 H335 May cause respiratory irritation.

· 2.2 Label elements

- · Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the CLP regulation.
- · Hazard pictograms



· Signal word Danger

• Hazard-determining components of labelling: methyl methacrylate ethyl methacrylate

(Contd. on page 2)

GB



Version number 4

Revision: 29.03.2022

Trade name: Thermosoft Lack

Printing date 29.03.2022

(Contd. of page 1) 2-ethylhexyl acrylate 2-hydroxyethyl methacrylate 2-Propenoic acid, reaction product with Pentaerythrite · Hazard statements H225 Highly flammable liquid and vapour. H315 Causes skin irritation. H319 Causes serious eve irritation. H317 May cause an allergic skin reaction. H335 May cause respiratory irritation. · Precautionary statements Keep away from heat, hot surfaces, sparks, open flames and other ignition P210 sources. No smoking. P241 Use explosion-proof [electrical/ventilating/lighting] equipment. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Store locked up. P405 P501 Dispose of contents/container in accordance with local/regional/national/ international regulations. · 2.3 Other hazards

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components: CAS: 80-62-6 methyl methacrylate 25-50% Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335 EINECS: 201-297-1 CAS: 97-63-2 ethyl methacrylate 10-25% Flam. Liq. 2, H225; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335 EINECS: 202-597-5 CAS: 103-11-7 2-ethylhexyl acrylate 2.5-10% EINECS: 203-080-7 Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335 CAS: 868-77-9 2-hydroxyethyl methacrylate 2.5-10% EINECS: 212-782-2 Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 Acrvlic resin ≤2.5% 🕩 Eye Irrit. 2, H319 CAS: 75980-60-8 Diphenyl(2,4,6-trimethylbenzoyl)phosphinoxide ≤2.5% EINECS: 278-355-8 🚸 Repr. 2, H361f CAS: 1245638-61-2 2-Propenoic acid, reaction product with Pentaerythrite ≤2.5% EC number: 629-850-6 🔶 Eye Dam. 1, H318; 🍫 Aquatic Chronic 2, H411; 🚸 Acute Ťox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317 · Additional information: For the wording of the listed hazard phrases refer to section 16.

(Contd. on page 3)



Revision: 29.03.2022

Printing date 29.03.2022

Version number 4

Trade name: Thermosoft Lack

(Contd. of page 2)

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Do not induce vomiting. Call a doctor immediately.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- \cdot 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam. Use fire extinguishing methods suitable to surrounding conditions.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- \cdot 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Avoid contact with skin and eyes. Wear protective equipment. Keep unprotected persons away.
6.2 Environmental precautions: Prevent seepage into sewage system, workpits and cellars. Do not allow to enter sewers/ surface or ground water.
6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
6.4 Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.



Revision: 29.03.2022

Printing date 29.03.2022

Version number 4

Trade name: Thermosoft Lack

(Contd. of page 3)

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Avoid contact with skin and eyes.
 Ensure good ventilation/exhaustion at the workplace.
 Prevent formation of aerosols.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Protect from heat and direct sunlight. Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:
- Store in cool, dry conditions in well sealed receptacles.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

80-62-6 methyl methacrylate

WEL Short-term value: 416 mg/m³, 100 ppm Long-term value: 208 mg/m³, 50 ppm

• Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

- Avoid contact with the eyes and skin. **Respiratory protection:**
- Do not inhale fumes.

Use suitable respiratory protective device in case of insufficient ventilation.

· Protection of hands:



Protective gloves

Protective gloves should be changed regularly, especially after intensive contact with the product. For every workplace a suitable type of protective gloves must be selected.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

Butyl rubber, BR

As there are many different conditions in every day work these indications can only serve as an aid to orientation for the selection of suitable gloves for the handling of chemical products. By no means they can replace qualifying examinations by the end-user.



Printing date 29.03.2022

Version number 4

Revision: 29.03.2022

Trade name: Thermosoft Lack

(Contd. of page 4) These recommendations only apply to the product mentioned in the safety data sheet. When mixing with other substances or under conditions deviant from norm EN 374 a manufacturer of CE-approved gloves should be referred to. The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed. The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended. · Eye protection: Tightly sealed goggles · Body protection: Protective work clothing SECTION 9: Physical and chemical properties 9.1 Information on basic physical and chemical properties General Information Appearance:

· Appearance:	
Form:	Fluid
Colour:	Colourless
· Odour:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
 Change in condition Melting point/freezing point: Initial boiling point and boiling range 	Undetermined. : 101 °C
· Flash point:	10 °C
· Flammability (solid, gas):	Not applicable.
· Ignition temperature:	245 °C
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	1.8 Vol %
Upper:	12.5 Vol %
 Oxidising properties 	Not determined
	Not applicable.
· Vapour pressure at 20 °C:	47 hPa
· Density at 20 °C:	1.0 g/cm ³
	(0

(Contd. on page 6)

⁻ GB



Printing date 29.03.2022

Version number 4

Revision: 29.03.2022

Trade name: Thermosoft Lack

	(Contd. of page
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Solids content:	0.0 %
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

• **10.1 Reactivity** No dangerous reactions if used according to specifications.

- 10.2 Chemical stability Stable if used according to specifications.
- Thermal decomposition / conditions to be avoided: Protect from heat and direct sunlight.

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Primary irritant effect:
- · Skin corrosion/irritation
- Causes skin irritation.
- Serious eye damage/irritation Causes serious eye irritation.
- Respiratory or skin sensitisation
- May cause an allergic skin reaction.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- \cdot Germ cell mutagenicity Based on available data, the classification criteria are not met.
- \cdot Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure
 - May cause respiratory irritation.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- \cdot Aspiration hazard Based on available data, the classification criteria are not met.

(Contd. on page 7)



Printing date 29.03.2022

Version number 4

Revision: 29.03.2022

Trade name: Thermosoft Lack

(Contd. of page 6)

SECTION 12: Ecological information

· 12.1 Toxicity

- Aquatic toxicity: No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:

· General notes:

Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · **vPvB:** Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

· European waste catalogue		
HP3	Flammable	
HP4	Irritant - skin irritation and eye damage	
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity	
HP13	Sensitising	

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information		
· 14.1 UN-Number · ADR, IMDG, IATA	UN1247	
· 14.2 UN proper shipping name		
ADR	1247 METHYL METHACRYLATE MONOMER, STABILIZED solution 1247 METHYLMETHACRYLAT, MONOMER, STABILISIERT, LÖSUNG	
· IMDG, IATA	METHYL METHACRYLATE MONOMER, STABILIZED solution	
	(Contd. on page 8)	



Printing date 29.03.2022

Version number 4

Revision: 29.03.2022

Trade name: Thermosoft Lack (Contd. of page 7) · 14.3 Transport hazard class(es) · ADR, IMDG, IATA · Class 3 Flammable liquids. · Label 3 · 14.4 Packing group · ADR, IMDG, IATA Ш · 14.5 Environmental hazards: · Marine pollutant: No · 14.6 Special precautions for user Warning: Flammable liquids. Danger code (Kemler): 33 · EMS Number: F-E,S-E Stowage Category В Stowage Code SW2 Clear of living quarters. · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable. · Transport/Additional information: · ADR · Limited quantities (LQ) 1L · Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml · Transport category 2 · Tunnel restriction code D/E · IMDG · Limited quantities (LQ) 1L · Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml · UN "Model Regulation": UN 1247 METHYL METHACRYLATE MONOMER, STABILIZED SOLUTION, 3, II

SECTION 15: Regulatory information

 \cdot 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

- Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

(Contd. on page 9)

GB



Version number 4

Revision: 29.03.2022

Trade name: Thermosoft Lack

(Contd. of page 8) • 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

Printing date 29.03.2022

H225 Highly flammable liquid and vapour.

- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H361f Suspected of damaging fertility.
- H411 Toxic to aquatic life with long lasting effects.
- · Department issuing SDS: Department Research & Development
- · Contact: Dr. Thomas Veit, Lothar Sutor, Susanne Weber

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA) ICAO: International Civil Aviation Organisation ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO) ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids - Category 2 Acute Tox. 4: Acute toxicity - oral - Category 4 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 Skin Sens. 1: Skin sensitisation - Category 1 Repr. 2: Reproductive toxicity - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Data compared to the previous version altered.